

^{15, 16}
a first frame section for mounting said roller rod, said first frame section
comprising a securing edge mounted to said side wall of one of said decorative parts;
^{12, 15}
a second frame section for receiving said pulling beam, said second frame section
comprising a securing edge mounted to said side wall of another of said decorative parts.

8. The device in accordance with claim 7 wherein said first and said second
frame sections extend in a vertical direction.

9. The device in accordance with claim 8 wherein said casing comprises an
inner wall and wherein said securing edge forms a seal abutting said inner wall of said casing.

10. The device in accordance with claim 7, and further comprising a threshold
comprising a threshold frame section provided with a U-shaped section for receiving said lower
end of said screen, said threshold further comprising a longitudinally extending side and a
gripping edge on said longitudinally extending side.

11. The device in accordance with claim 10, and further comprising a threshold
section adapted to be mounted to a sloping threshold surface and at least one support
rib of a predetermined height for engagement with a threshold having a sloping upper surface and
at least one projecting section edge for engagement with said threshold frame section.

12. The device in accordance with claim 7, wherein said casing comprises an
upper frame section comprising a U-shaped guide section having a slotted opening and wherein
said pulling beam has an upper end and a suspension element having opposing ends, one of said
opposing ends adjustably mounted to said upper end of said pulling beam and an other of
said opposing ends engaging said U-shaped guide section.